

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 7281341 B2  
APPLICATION NO. : 10/732,834  
ISSUE DATE : 10/16/07  
INVENTOR(S) : REAGAN, GREG

1 of 8

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

The Title Page, showing an illustrative figure, should be deleted and substitute therefor the attached Title Page.

Delete drawings sheets 1-6 and substitute therefor the drawing sheets, consisting of figs. 1-8 as shown on the attached page.



US007281341B2

**(12) United States Patent**  
**Reagan et al.****(10) Patent No.: US 7,281,341 B2**  
**(45) Date of Patent: Oct. 16, 2007****(54) LACE SYSTEM FOR FOOTWEAR**

1,246,724 A 11/1917 Daggett

- (75) Inventors:**
- Greg Reagan, Essex, VT (US);
- 
- Christopher M. Doyle, Waterbury, VT
- 
- (US); Florian Lang, Colchester, VT
- 
- (US); Maurizio Molin, Venice (IT)

(Continued)

## FOREIGN PATENT DOCUMENTS

- (73) Assignee:**
- The Burton Corporation, Burlington,
- 
- VT (US)

DE 3626837 2/1988

- (\*) Notice:**
- Subject to any disclaimer, the term of this
- 
- patent is extended or adjusted under 35
- 
- U.S.C. 154(b) by 287 days.

(Continued)

## OTHER PUBLICATIONS

- (21) Appl. No.:**
- 10/732,834

Internet web page advertising Rollerblade Aero 9 product, printed  
on May 13, 2003.

- (22) Filed:**
- Dec. 10, 2003

(Continued)

- (65) Prior Publication Data**

US 2005/0126043 A1 Jun. 16, 2005

*Primary Examiner*—Marie Patterson  
(74) *Attorney, Agent, or Firm*—Wolf, Greenfield & Sacks  
P.C.

- (51) Int. Cl.**
- 
- A43C 11/00*
- (2006.01)
- 
- A43B 5/04*
- (2006.01)

**(57) ABSTRACT**

- (52) U.S. Cl.**
- ..... 36/50.1; 36/50.5
- 
- (58) Field of Classification Search**
- ..... 36/50.1,
- 
- 36/50.5, 117.1, 136

See application file for complete search history.


A boot incorporating techniques for making the process of tightening and loosening the laces of a boot more convenient for the wearer is disclosed. The boot may be provided with at least two independent lacing zones, the tensions of which are separately adjustable by the wearer. The zones may be secured by pulling on two laces, each of which tightens one of the two independent lacing zones. This arrangement allows the wearer to simultaneously tighten each zone, providing the wearer with the "feel" as though he or she is tightening a conventional single lacing zone boot. The laces may be simultaneously, yet independently secured by a lace lock at the upper and/or forward region of the boot. Slack may be created to facilitate loosening of the boot and easy removal of a foot from the boot by unhooking the lace from the lace guide without a corresponding distance of lace traveling through the lace lock. A release strap, graspable by the wearer, facilitates unhooking the lace.

- (56) References Cited**

## U.S. PATENT DOCUMENTS

375,677 A	12/1887	Kyle
547,424 A	10/1895	Eaton
586,770 A	7/1897	Kempshall
599,906 A	3/1898	Kempshall
654,388 A	7/1900	Diemer
714,191 A	11/1902	Kempshall
737,769 A	9/1903	Preston
742,206 A	10/1903	Maurer
795,119 A	7/1905	Harlow
1,053,529 A	2/1913	Neary
1,090,438 A	3/1914	Worth et al.
1,242,774 A	10/1917	Curry

124 Claims, 6 Drawing Sheets






Fig. 1

*Fig. 2*

*Fig. 3*





Fig. 4

**Fig. 5**




Fig. 6




Fig. 7




Fig. 8